

Colours, Active Programs, and Coordinate Transforms



Key Points



- 1) Color background, shapes, text
- 2) Control transparency
- 3) Understand two basic color modes: RGB vs HSB
- 4) Set color range

Color Representation

- You can use different colors for your drawings and the background.
- You have two options:
 - **Grayscale**: different shades of gray
 - A single digit (integer) ranging from 0 (black) to 255 (white)




- **Color**: to represent a required color using a color model such as RGB or HSB (aka HSV).

RGB Color Model

- RGB is a color that is a result of mixing three primary colors, Red, Green, and Blue.
 - The amount of each color is represented by a value from 0 (none) to 255 (max).

- Examples:



	RED Component	GREEN Component	BLUE Component
<i>Red</i>	255	0	0
<i>Green</i>	0	255	0
<i>Blue</i>	0	0	255
<i>White</i>	255	255	255
<i>Black</i>	0	0	0
<i>Yellow</i>	255	255	0
<i>Cyan</i>	0	255	255
...	...	...	...


- Note: when you have same amounts, you get a shade of gray

Color Question



What is the best description of RGB color (210,0,190)?

- A. a shade of purple
- B. a shade of yellow
- C. a shade of blue
- D. a shade of green
- E. a shade of gray




Color Question



What is the best description of RGB color (120,120,120)?

- A. a shade of purple
- B. a shade of yellow
- C. a shade of blue
- D. a shade of green
- E. a shade of gray



How to Color?

- You can color the following items:
 - **background** using **background()** function.
 - **outline** and **fill** of a shape using **stroke()** and **fill()** before drawing the shape.
- Use either
 - one argument for gray shades. e.g. **fill(0)** is *black* fill.
 - three arguments for RGB color. e.g. **fill(255,0,0)** is *red* fill
 - Note that RGB mode is used by default.
- Once you set a color, it applies to *all shapes drawn afterwards*.
- **Default values** are used if no colors are chosen.
 - **background**: 204 (light gray), **stroke**: 0(black), **fill**: 255 (white).
- You can use **noFill()** or **noStroke()** functions to disable filling or outlining a shape.

List of color functions so far...

- ▣ **background()**
 - ▣ Set background color
- ▣ **stroke(), noStroke()**
 - ▣ Set stroke (line) color
- ▣ **fill(), noFill()**
 - ▣ Set filling or text color

Colourful Shapes


```
background(128);

strokeWeight(3);

fill(255);
rect(0,0,90,40);

stroke(255, 0, 0);
fill(0);
rect(10,20,30,30);

stroke(255, 0, 255);
fill(255, 0, 0);
rect(50,20,30,30);
```



Q: Can you link each statement to one of the output shapes?

Colourful Text

```
background(0);  
size(140,120);  
  
textAlign(CENTER);  
textSize(28);  
text("UBC", 70, 30);  
  
textSize(18);  
text("Okanagan", 70, 50);  
  
fill(255,255,0);  
textSize(12);  
text("Computer Science", 70, 70);  
  
fill(0,255,0);  
textSize(10);  
text("1177 Research Rd, Kelowna, BC V1V 1V7", 10,85,120,40);
```



Colour Transparency

- An *optional argument* can be used for `fill()` and `stroke()` to *control transparency*.
 - 0 completely transparent i.e. 0% opacity
 - 255 completely opaque i.e. 100% opacity
- Examples:
 - `fill(255)` is opaque white filling (default opacity is 100%)
 - `fill(0, 128)` is semi-transparent black filling
 - `fill(255, 0, 0, 128)` is semi-transparent red filling

```
background(128);  
fill(255);  
rect(0,0,70,20);  
fill(0, 128);  
rect(10,10,20,20);  
fill(255, 0, 0, 128);  
rect(40,10,20,20);
```



Using Colours



What will be drawn on the screen?

- A. A line, rectangle, and an ellipse
- B. A rectangle and an ellipse
- C. Only the ellipse
- D. Nothing
- E. This code has an error and won't run.

```
noStroke();  
line(30,30,50,30);  
noFill();  
rect(10,10,20,20);  
stroke(255,0);  
ellipse(50,50,20,20);
```


Using Colours



These two statements are exactly the same.

```
fill(255,255,255);
```


```
fill(255,255);
```

A. True

B. False

Use Colours!

- Write a code to create the following sketch +2 points



Aside: Hexadecimal Notation

- RGB colours can be represented using Hexadecimal notation.
 - Syntax: #RRGGBB
 - The # denotes the hex notation
 - RR is a two-digit hex number representing red value from 0 to 255
 - GG is a two-digit hex number representing green value from 0 to 255
 - BB is a two-digit hex number representing blue value from 0 to 255
- Examples:
 - fill(255, 255, 255) equivalent to fill(#FFFFFF)
 - fill(128, 196, 64) equivalent to fill(#80C440)
 - fill(0, 0, 255) equivalent to fill(#0000FF)

HSB Colour Model

- In this mode, a colour is represented by three components

- **Hue**

- Dominant pure color.



- **Saturation:**

- Vibrancy of the color
 - Range: 0 to 100

- **Brightness**

- How bright the color is.
 - Range: 0 to 100





Image adapted
from wikipedia




A plane with all S and B
values for Hue=0 (red)

Colour Question



What is the best description of HSB colour (350,90,95)?

- A. a shade of red
- B. a shade of blue
- C. Black
- D. White
- E. One of the ranges is invalid




Note: Assume the ranges (0-360,0-100,0-100)

Colour Question



What is the best description of **HSB** colour (300,0, 50)?

- A. a shade of red
- B. a shade of blue
- C. a shade of gray
- D. black
- E. One of the ranges is invalid




Note: Assume the ranges (0-360,0-100,0-100)

Colour Question



What is the best description of HSB colour (300, 99, 0)?

- A. a shade of red
- B. a shade of blue
- C. a shade of gray
- D. black
- E. One of the ranges is invalid




Note: Assume the ranges (0-360,0-100,0-100)

Colour Question



What is the best description of HSB colour (200,0,150)?

- A. a shade of red
- B. a shade of blue
- C. Black
- D. White
- E. One of the ranges is invalid




Note: Assume the ranges (0-360,0-100,0-100)

Colour Question




These two HSB colours look the same on the screen:
(200,0,50) and (50,0,50)

- A. True
- B. False



HSB Ranges in Processing

- While above ranges (i.e. 360,100,100) are standard in image processing, the *Processing language* uses **255,255,255** by default.



Changing the Color Mode

- By default, processing uses RGB mode with ranges from 0 to 255 for all color components R, G, and B.
- Defaults can be changed using `colorMode()` function.

- Syntax:

```
colorMode(mode)
colorMode(mode, max)
colorMode(mode, max1, max2, max3)
colorMode(mode, max1, max2, max3, maxA)
```

- Examples:

- `colorMode(RGB)` RGB mode, use **default** ranges (0 to 255)
- `colorMode(RGB, 100)` RGB mode, ranges: 0 to 100 for all colors
- `colorMode(HSB)` HSB mode, default ranges 0 to 255)
- `colorMode(HSB, 360, 100, 100)` change defaults to 360, 100, 100
- `colorMode(HSB, 1)` HSB, ranges 0 to 1.0 for all components
- `colorMode(HSB, 1, 1, 1, 10)` same as above, opacity is 0 to 10.

Changing the Colour Mode, cont'd

Be careful:

After changing the ranges with any of the statements above, those ranges will remain in use until they are explicitly changed again.


```
colorMode(RGB, 100, 100, 100); //ranges are 100 for all R,G,B components  
colorMode(HSB);                //ranges are still 100 for all H,S,B components
```

List of colour functions we learned today


- **background()**
 - Set background colour
- **stroke(), noStroke()**
 - Set stroke (line) colour and transparency
- **fill(), noFill()**
 - Set filling or text color and transparency
- **colorMode()**
 - Choose between RGB and HSB, and optionally set the range

Examples

```
size(140, 40);  
background(0);  
noFill();  
colourMode(HSB, 100);  
for (int i = 0; i <= 100; i+=10) {  
    stroke(i, 100, 100); //only change the hue in every iteration  
    ellipse(i+20, 20, 30, 30);  
}
```




```
// this example is from Processing Documentation  
colourMode(RGB, 100);  
for (int i = 0; i < 100; i++)  
    for (int j = 0; j < 100; j++) {  
        stroke(i, j, 0);  
        point(i, j);  
    }
```



Note: don't worry so much if you don't remember for loops. We will go over it later.

PDE Colour Selector Tool

- You can use the PDE colour selector tool from the tools menu (**Tools->Color Selector...**) to get the values of your chosen color.



Update Your Design

- Add code to your character that you designed previously so that it has colours now 😊... remember, be creative with your colors and shapes.
- Here is my design, but yours should be different



Active Programs



Objectives

- This is a pre-class reading materials.
- After finishing reading the materials, you should be able to:
 - Understand the difference between **static** and **active** modes.
 - Understand the order of execution of active sketches.
 - Create a simple animation using `setup()` and `draw()`.
 - Set the frame rate of an animation using `frameRate()`
 - Know where to place `size()` and `background()`
 - Use the system variables: `mouseX`, `mouseY`, `width`, `height`
 - Stop an animation using `noLoop()`




Static vs Active Modes

- All programs you have been writing so far are **static** sketches.
 - A **static sketch** is a series of statements that aim to draw a **single image**; i.e. no animation or interaction.
- An **active** sketch on the other hand aims to draw a **series of images** (each called a **frame**) that represent an **animation**.
- Active sketches may be programmed to be **interactive** to user's actions.
 - Examples of actions: mouse movement, keyboard presses, etc.

How to Create Active Sketches

- Two **built-in** functions: `setup()` and `draw()` are always **called automatically**.
 - `setup()` runs once at the beginning
 - Then `draw()` runs repeatedly.
- The rate of running the `draw` method is called the **framerate**.
 - The default is **60 fps**, but it can be changed using the `frameRate()` function.
- You can **stop** repeating `draw()` using `noLoop()` function.



Active Program Structure

This part **runs once** and is used for **initialization**

```
void setup() {  
  // Step S1  
  // Step S2  
  // ...  
  // Step Sn  
}
```

The two curly brackets **{ }** are used to define the beginning and end of a block of code

This part **loops forever** and is used for **animation**

```
void draw() {  
  // Step D1  
  // Step D2  
  // ...  
  // Step Dn  
}
```

Order of execution: **S₁, S₂, ..., S_n, D₁, D₂, ..., D_n, D₁, D₂, ..., D_n, D₁, ...etc**

Drawing a Static Sketch with setup/draw

- All these four programs produce the same output
 - *Justify?*

without setup/draw

```
size(200,200);  
background(255);  
rect(10,10,40,40);
```



three different ways with setup/draw

```
void setup(){  
  size(200,200);  
}  
void draw(){  
  background(255);  
  rect(10,10,40,40);  
}
```

```
void setup(){  
  size(200,200);  
  background(255);  
}  
void draw(){  
  rect(10,10,40,40);  
}
```


```
void setup(){  
  size(200,200);  
  background(255);  
  rect(10,10,40,40);  
}
```

Notes About Active Sketches

- You can't mix static and active modes!
 - Once you use active mode, you can't call any function, such as `rect()`, outside `setup()` and `draw()`.
- `size()` can only be executed once
 - so it can't be part of `draw()`

mix static & active

```
void setup(){
  size(200,200);
}
void draw(){
  background(255);
  rect(10,10,40,40);
}
```



```
rect(10,10,40,40);
void setup(){
  size(200,200);
}
void draw(){
  background(255);
}
```



wrong place for size()

```
void setup(){
}
void draw(){
  size(200,200);
  background(255);
  rect(10,10,40,40);
}
```




Mouse Location

- Processing has two keywords (*system variables*) that will always contain the current coordinates of the mouse cursor.
 - `mouseX` and `mouseY` contain mouse location (x,y) in current frame.
 - *Default value* is 0 for both variables.

A Shape Following the Mouse

- In this example, the ball follows the mouse position.

```
void setup() {  
  size(200, 200);  
  stroke(255);  
  strokeWeight(3);  
}  
void draw() {  
  background(0,63,107);  
  fill(255,0,102);  
  rect(50,50,100,100);  
  fill(0,192,255,130);  
  ellipse(mouseX, mouseY, 80, 80);  
}
```



Where to put *background()*



- *If placed in draw()*, it clears the sketch at beginning of every frame
 - i.e. it flood the sketch with some color.
- *If placed in setup()*, it sets the background of first frame only and doesn't clear subsequent frames.
- If you move `background()` to `setup()`, this would be the output from the previous example.

```
void setup() {  
  size(200, 200);  
  stroke(255);  
  strokeWeight(3);  
  background(0, 63, 107);  
}  
void draw() {  
  fill(255, 0, 102);  
  rect(50, 50, 100, 100);  
  fill(0, 192, 255, 130);  
  ellipse(mouseX, mouseY, 80, 80);  
}
```



Window's width and height


- There are two more useful system variables: **width** and **height** that contain the size of the current display window.
 - We set these two values using the **size()** function.
 - Default value is 100 if **size()** is not used.



Two Shapes Controlled by the Mouse

In this example, we create a second ball positioned at the inverse of the cursor position.

```
void setup() {  
  size(200, 200);  
  stroke(255);  
  strokeWeight(3);  
}  
  
void draw() {  
  background(0,63,107);  
  fill(255,0,102);  
  rect(50,50,100,100);  
  fill(0,192,255,130);  
  ellipse(mouseX, mouseY, 80, 80);  
  fill(255,192,0,130);  
  ellipse(width-mouseX, height-mouseY,80,80);  
}
```





Function Automatically Called

Which of these functions is *automatically called* by the system once we run the program?

- A. `size(200,200);`
- B. `setup()` and `draw()`
- C. `noLoop()`
- D. `rect(0,0,width,height);`
- E. `ellipse(0,0,width,height);`

Frame Rate



The default frame rate is _____ and it can be changed using the function _____

- A. 15, frameRate()
- B. 60, frameRate()
- C. 15, setFrameRate()
- D. 60, setFrameRate()
- E. None of the above



Where to write code?

Which code is valid?

A.

```
void setup(){
    ...
}
void draw(){
    size(100,100);
    ...
}
```

B.

```
void setup(){
    size(100,100);
    ...
}
void draw(){
    ...
}
```

C.

```
size(100,100);
void setup(){
    ...
}
void draw(){
    ...
}
```

D. None of the above.



Where to write code?

Which code clears a the display window at the beginning of each frame?

A.

```
void setup(){
  size(200,200);
}
void draw(){
  background(255);
  rect(5,5,90,90);
}
```

C.

```
background(255);
void setup(){
  size(200,200);
}
void draw(){
  rect(5,5,90,90);
}
```

B.


```
void setup(){
  size(200,200);
  background(255);
}
void draw(){
  rect(5,5,90,90);
}
```

D. None of the above; I have a better answer.

Question: what is the difference between A, B, and C?

Tweaking Your Sketch At the Runtime

- Tweak Mode (**Sketch->Tweak**) runs the code so that you can change some color and variable values while the code is running and see instant feedback.
- Notes:
 - This only applies to **active mode**.
 - You need to save your program before you can tweak it.




Animation based on Mouse Location

- Build on the code in the pre-class materials and use the mouse coordinates (`mouseX`, `mouseY`) to control other attributes in the animation, e.g. size, transparency, color, background, etc.

- **Be creative!** For example, in this animation →

- I added a third circle, then had the size of each shape change differently:
 - Circle1: $\text{radius} = \text{mouseX} + \text{mouseY}$
 - Circle2: $\text{radius} = \text{mouseX}/2$
 - Circle3: $\text{radius} = \text{mouseY} * 2$
 - Box: size depends on `mouseX` and `mouseY`
- Controlled shapes' location with mouse location.
- Changed the background color based on the combined size of all circle.




+3 points

- Your interactive animation doesn't have to have any purpose for now, just try to make it look cool and have fun 😊

Moving *YOUR* Character

- Referring to the character you designed previously, add code to your program so that the character moves with your mouse cursor.
- Hint: the location of all shapes of your character should depend on `mouseX` and `mouseY`
- Here is the output (Your character could be different):



+3 points

Pre-Class Reading

Active Programs (2)



Objectives

- This is a pre-class reading materials. After reading them, you should be able to:
 - Use mouse location from previous frame (`pmouseX`, `pmouseY`)
 - Generate random numbers using `random()`
 - Write programs that are driven by mouse and key events
 - 1) Using mouse functions:
`mousePressed()`, `mouseReleased()`, `mouseClicked()`,
`mouseMoved()`, `mouseDragged()`
 - 2) Using key functions:
`keyPressed()`, `keyReleased()`




Mouse Location... revisited!

- You have seen before that Processing has two *system variables* that hold the current coordinates of the mouse cursor
 - `mouseX` and `mouseY` contain mouse location (x,y) in current frame.
- Furthermore, processing has two more system variables that will always hold the previous coordinates of the mouse cursor.
 - `pmouseX` and `pmouseY` contain (x,y) from the frame previous to the current frame (if used inside the `draw()` function).
- **Default value** is 0 for all four variables.

pmouseX and pmouseY

- You can use pmouseX and pmouseY whenever you want to use the mouse location in the previous frame.



Example 1

pmouseX and pmouseY

- We can use previous mouse coordinates to draw a *continuous line*.
- Note where we placed `background`.

```
void setup() {  
  size(200, 200);  
  background(255); // don't clear previous frame  
}  
void draw() {  
  line(pmouseX, pmouseY, mouseX, mouseY );  
}
```




- **Task:** change the *framerate* to 4 fps and check the output

Mouse and Key Events

- While `setup()` & `draw()` are **always** invoked automatically, there are functions that are invoked **based on users input**.
- Functions that are called based MOUSE events:
 - `mousePressed()`: called whenever a mouse button is clicked
 - `mouseReleased()`: called whenever a mouse button is released
 - `mouseClicked()`: called after a mouse button is pressed then released.
 - `mouseMoved()`: called whenever the mouse moves and the mouse button **is not** clicked
 - `mouseDragged()`: called whenever the mouse moves and the mouse button **is** clicked
- Functions that are called based KEY events:
 - `keyPressed()`: called whenever a key is pressed.
 - `keyReleased()`: called whenever a key is released.

Overall Structure of Active Programs



Event Driven Program

- In this example, a new circle is drawn *whenever the mouse is clicked*. The color of the circle is random.
- Also, *whenever a key is pressed*, the sketch is cleared!

```
void setup() {  
  size(200, 200);  
  colorMode(HSB,360,100,100);    //HSB mode is used  
  background(360,0,100);          //white background  
  noStroke();  
}  
void draw() { // nothing here}  
  
void mousePressed() {  
  fill(random(360),100,100,128); //random color  
  ellipse(mouseX, mouseY, 40, 40);  
}  
void keyPressed() {  
  background(360,0,100);          //clear sketch  
}
```



Question: what happens if we add `background()` to `draw()`?

Active Programs (2)



The Pre-Class Reading

- The pre-class materials covered the following:
 - **New** keywords: `pmouseX`, `pmouseY`
 - **New** functions : `random()`
 - **New** event-driven functions
 - automatically invoked based on MOUSE events:
`mousePressed()`, `mouseReleased()`, `mouseClicked()`,
`mouseMoved()`, `mouseDragged()`
 - automatically invoked based on KEY events:
`keyPressed()`, `keyReleased()`

Mouse Location



Which of the following keeps track of mouse location from previous frame?

- A. `mouseX` , `mouseY`
- B. `pmouseX` , `pmouseY`
- C. `pFrame.x`, `pFrame.y`
- D. `pFrame.mouseX`, `pFrame.mouseY`
- E. none of the above

Drawing a continuous line



Which of the following can be used to draw a continuous line?

A.

```
void setup(){ background(255); }  
void draw() {  
  line(pmouseX, pmouseY , mouseX, mouseY);  
}
```

B.

```
void setup(){ background(255); }  
void draw() {  
  line(mouseX, mouseY, pmouseX, pmouseY );  
}
```

C.

```
void setup(){ }  
void draw() {  
  background(255);  
  line(mouseX, mouseY, pmouseX, pmouseY );  
}
```



- D. *Either A or B*
- E. *All of them*



Event Based Programming

Which of these functions is automatically called whenever the user presses the mouse button and moves the mouse at the same time.

- A. mouseReleased
- B. mousePressed
- C. mouseDragged
- D. mouseMoved
- E. Both B and C


Framerate



Which framerate has most probably produced this output?

- A. 60
- B. 45
- C. 30
- D. 25
- E. 5

```
void setup() {  
    size(200, 200);  
    background(255);  
    stroke(0);  
    framerate(????);  
}  
void draw() {  
    line(pmouseX, pmouseY, mouseX, mouseY);  
}
```



Mouse Speed


- this code is from the pre-class readings and is used to draw a continuous line.

```
void setup() {  
  size(200, 200);  
  background(255);  
  stroke(0);}  
void draw() {  
  //... add code here ...  
  line(mouseX, mouseY, pmouseX, pmouseY );  
}
```
- Modify the code so that the thickness of the line is controlled by the **mouse speed**. Here are some hints:
 - Mouse Speed is the distance the mouse travel per unit of time. Therefore, speed can be computed in terms of the distance the mouse travels in each new frame.
 - i.e. difference between current mouse position and previous one
 - Use `abs()` function to avoid negative values.
 - Don't worry too much about having accurate calculations.




Mouse Events

- Create a program that draws a circle which follows the mouse (same location as the mouse)
- The circle should be:
 - red with thick, yellow outline as long as the mouse is pressed.
 - green with thin, white outline as long as the mouse is not pressed.
- Don't use variables or conditional statements




Mouse key is not pressed



Mouse key is pressed

Aside: *smooth()* and *noSmooth()*

- By default, all geometry is drawn with smooth (anti-aliased) edges. However, you can control this behaviour using **smooth()** function to enable this feature, and **noSmooth()** function to disable smoothing.
- Notes:
 - You don't need to run **smooth()** as it is the default behaviour.
 - You may use it if you want to change the anti-aliasing level (1,2,4,8) – the default level 2; i.e. **smooth(2)**
 - The maximum anti-aliasing level is determined by the hardware of the machine running the software
 - i.e. no guarantee that **smooth(4)** and **smooth(8)** will work on your computer.
 - Use both functions inside the **setup()** function.



Coordinates Transformation




Key Points



- 1) How to translate, rotate, and scale the coordinates
- 2) Coordinates are reset before every new frame.
- 3) Transformation is cumulative *within* each frame.
- 4) Order is important when combining more than one transformation.
- 5) Storing and restoring coordinate systems.
- 6) How to use transformed coordinates in static and dynamic programs.


The **Default** Coordinate System

- By default, the coordinate system has its **origin** at the upper-left corner of the window, with x and y coordinates as shown in the figure.
- This default representation can be transformed, i.e. **translated**, **rotated**, and scaled using built-in functions:
 - translate()**, **rotate()**, **scale()**
- Only shapes drawn **after** the transformation use the new coordinates.
- Coordinates are **reset at the beginning** of each new frame (inside `draw()`)



Coordinate Translation - `translate()`

- The `translate()` function moves the origin to a new location.




- `translate()` applies only to shapes drawn after the function call
- You can think of `translate` as if you are **adding its arguments** to all shapes that come after it. i.e. $(30, 10) + (40, 40) = (70, 50)$

Example 1

translate() in static mode


```
// move origin 30 px right and 20 px down  
translate(30, 20);  
fill(0,255,0);  
rect(0, 0, 40, 40); // Draw at new origin
```




- **Remember** that we can think of the output as if we add the translation value to the location of rectangle (assuming the original is still at top-left corner). That is,
 - The (x,y) of the green rectangle is $(0+30, 0+20)$ if the original is still at top-left corner.

Coordinate Translation - *translate()*

- `translate()` is **cumulative** within each frame.



- However, the coordinates are **reset** for each new frame.
 - i.e. if you use transform the coordinates within `draw()` method, the next frame assumes default origins and then translate again.




Example 2

translate() in static mode

```
// Draw rect at default origin
fill(255,0,0);      // Red
rect(0, 0, 40, 40);

// move origin 30 px right and 20 px down
translate(30, 20);
fill(0,255,0);      // Green
rect(0, 0, 40, 40); // Draw at new origin

// move origin again 20 px left and 50 px down
translate(-20, 50);
fill(0,0,255);      // Blue
rect(0, 0, 40, 40); // Draw rect at new
```




- **Another way** of thinking of the output is that we **add the translation** value to the location of shapes drawn after the function call. That is,
 - The (x,y) of the **green** rectangle is **(0+30,0+20)**
 - The (x,y) of the **blue** rectangle is **(0+30-20,0+20+50)**

Example 3

translate() in dynamic mode



```
void draw() {  
    // every beginning of new frame, default origin at (0,0) is used  
    fill(0,255,0);           // Green  
    rect(0, 0, 40, 40); // Draw rect at new origin  
  
    translate(50, 30);       // move origin to (50, 30)  
    fill(0,0,255);           // Blue  
    rect(0, 0, 40, 40); // Draw rect at new origin  
}
```



Example 4

Moving all items with the mouse

```
void draw() {  
    background(255);  
    // Translate to the mouse location  
    translate(mouseX, mouseY);  
    ellipse( 30,  30, 6, 6);  
    ellipse(-30,  30, 6, 6);  
    ellipse( 30, -30, 6, 6);  
    ellipse(-30, -30, 6, 6);  
}
```




Q1: is there another way to write the code **without** `translate()`?

Q2: what is the **benefit** of using `translate()` over the other method?
(remember the exercise of moving your character with the mouse)

Coordinate Rotation - `rotate()`


- The `rotate()` function rotates the axes to a new angle.
- It has one parameter, the angle specified in radians.
- Similar to `translate()`, `rotate()` is cumulative and applies only to shapes drawn **after** the function call.



- Note: `rotate(PI)` is the same as `rotate(radians(180))`


Coordinate Rotation - `rotate()`

- The `rotate()` function rotates the axes to a new angle.
- It has one parameter, the angle specified in radians.
- Similar to `translate()`, `rotate()` is cumulative and applies only to shapes drawn **after** the function call



rotate() Example


```
size(150, 150);  
background(0);  
noFill();  
stroke(0, 255, 0); // green outline  
rectMode(CENTER);  
  
translate(75, 75); // origin at sketch center  
  
rotate(PI/6);      // rotate 30 degrees  
rect(0, 0, 40, 40);  
  
rotate(PI/6);      // rotate 30 degrees more  
rect(0, 0, 40, 40);  
  
rotate(PI/6);      // rotate 30 degrees more  
rect(0, 0, 40, 40);
```



Q. Link statements to shapes in sketch.

Coordinate Scaling - *scale()*

- The *scale()* function scales the coordinate system so that shapes are drawn in a different scale (this also affects pixel and border size).
 - Two functions: *scale(size)* and *scale(xsize, ysize)*
- Similar to other transforms, *rotate()* is cumulative and applies only to shapes drawn after the function call



scale() Example


```
size(150, 150);

scale(0.5); // scale is 50%
rect(10, 10, 20, 20);

scale(2); // now scale is back to 100%
rect(10, 10, 20, 20);

scale(2); // scale is 200%
rect(10, 10, 20, 20);

scale(2); // scale is 400%
rect(10, 10, 20, 20);
```




Q. Link statements to shapes in sketch.

Order Matters!

Order is important when combining more than one transformation.


- In the first example, the coordinates are translated first then rotated

```
// translate then rotate  
translate(50, 50);  
rotate(PI/6);  
rect(0, 0, 30, 30);
```



- In the second example, the coordinates are rotated first then translated.

```
// rotate and translate  
rotate(PI/6);  
translate(50, 50);  
rect(0, 0, 30, 30);
```



Storing and Restoring Coordinates

- The coordinate system is saved as a transformation matrix.
- You can use `pushMatrix()` and `popMatrix()` to store and restore the current coordinate system.
- Example:


```
size(150,150);

pushMatrix();    // save current origin

translate(50, 50); //origin at (50,50)
fill(255,0,0);   //red
rect(10,10,40,40);

popMatrix();     //retrieve last stored origin

fill(0,255,0);   //green
rect(10,10,40,40);
```



Aside: stacking transformations

- You can use `pushMatrix()` and `popMatrix()` multiple times
 - This case, they will be added/removed using the “matrix stack”.


```
size(150,150);

pushMatrix();      // save default origin
translate(50, 50); //origin at (50,50)
fill(255,0,0); rect(0,0,40,40); //red

pushMatrix();      // save current transformation
translate(50,50);  // origin at (100,100)
fill(0,255,0); rect(0,0,40,40); //green


popMatrix();       // restore prev origin - (50,50)
fill(0,0,255); rect(0,0,20,20); //blue

popMatrix();       // restore original origin (0,0)
fill(0); rect(0,0,10,10); //black
```



Coordinate Transformation

- [3 points] Write code to produce the output below. You can only use `rect()` and `ellipse()` functions to draw the shapes. All shapes must be located at $(x,y) = (0,0)$, i.e. the origin of the shape is $(0,0)$ – use coordinate transformation to place the shapes.




Moving *YOUR* Character using *transform()*

[1 point] **Previously**, you moved your character by adding `mouseX` and `mouseY` to every (x,y) of all shapes in your character.

Today, we will move the character using a simpler technique.

- 1) copy your character code from Exercise2 in the “Color” slides
- 2) add one statement at the beginning to move (translate) your character.



Pre-Class Reading

Variables, Data Types, and a bit of Math

Part(A)



Objectives



- This is a pre-class reading materials. After reading them, you should be able to:
 - Define value, variable, and memory location
 - Create and use variables of different data types
 - recognize the naming rules and guidelines for variables.
 - List and compare the data types in processing.
 - Define and use the “color” type.
 - Creating and using constants.
 - Properly use math operators.
 - Evaluate math expressions.





Values, Variables, and Locations

- A **value** is a data item that is manipulated by the computer.
- A **variable** is the name that the programmer uses to refer to a location in memory.
- A **location** has an address in memory and stores a value.



Values, Variables, and Locations

- Let's say we want to store a number that represents the age.

- Step #1: Declare** variable by giving it a NAME and a TYPE.

```
int age;    // age can only store integers
```

- The computer allocates space for the variable in memory (at some memory address). Every time we give the name `age`, the computer knows what data item we mean.

- Step #2: Initialize** the variable to have a starting value. E.g.,

```
age = 21;
```

- Step #3:** Value stored in a location can be changed throughout the program to whatever we want using **assignment** ("=" symbol).

```
age = age + 3;
```

Variable Name Lookup Table

<u>Name</u>	<u>Location</u>	<u>Type</u>
age	16	int

16

20

24

Memory

??? 21 24

Variable Name

- A variable must have a **NAME** and a **TYPE**.
- Names (aka *identifiers*):
 - **are case sensitive** (*B* is not the same as *b*)
 - can be a sequence of characters that include only *letters*, *digits*, *underscores* (`_`), and *dollar signs* (`$`).
 - must start with a letter, an underscore (`_`), or a dollar sign (`$`).
 - cannot start with a digit.
 - can **not** be a reserved word.
 - E.g. cannot be called `double`, `true`, `false`, or `null`.
 - Naming guidelines
 - can be of any length, but reasonable (readable) length is preferred.
 - should start with a lower case letter.
 - if more than one word, remove the spaces and capitalize all words after the first one (e.g. `my first car` → `myFirstCar`)

Variable Type

- A variable must have a ***name (identifier)*** and a ***type***. Each type has a valid range of values and uses a different amount of memory space.

	Type	Size in memory	Range
whole numbers	byte	8 bits	-2^7 to 2^7-1 (-128 to 127)
	short	2 bytes	-2^{15} to $2^{15}-1$ (-32768 to 32767)
	int	4 bytes	-2^{31} to $2^{31}-1$
	long	8 bytes	-2^{63} to $2^{63}-1$
real numbers	float	4 bytes	e.g. 17.345f
	double	8 bytes	e.g. 12452.212 (more accurate)
characters	char	2 bytes	e.g. 'a', '1' and '?'
boolean	boolean	1 byte	true or false

- **Note:** Unlike JavaScript, where you don't specify a type (i.e. just use var), in Java (and Processing) you must specify the variable type.

The String Type

- **Strings** are sequences of characters inside double quotes (i.e. text in double quotes).
- Example:

```
String personName = "Abdallah Mohamed";  
personName = "John Smith";
```

 - The first statement creates (defines) a variable and initializes its value to "Abdallah Mohamed".
 - The second statement is assigns a new value to existing variable.
- The **concatenation operator** is used to combine two strings into a single string. The notation is a plus sign '+'.

```
String firstName = "Abdallah", lastName = "Mohamed";  
String fullName = firstName + lastName;
```

The Color Type

- Processing introduces a new data type called **color** which stores color information. The value of a color variable can be set by the **color()** function.

```
color red = color(255,0,0);      // red in RGB mode
color navy = color(#443F76);    // navy in hex notation (RGB)
colorMode(HSB,360,100,100);

color green = color(128,100,100); // green in HSB mode
color blue = color(#0011FF);     // blue in hex notation (RGB)
```

```
background (navy);    // navy background
```

```
fill(red);
rect(10,10,40,40);    // red square
```

```
fill(green);
rect(50,50,40,40);    // green square
```

```
fill(blue);
ellipse(75,25,30,30); // green square
```

red uses RGB as it was defined before changing the color mode

blue uses RGB even though it was defined after setting the color mode because **blue** was defined using hex notation

Declaring and Initializing Variables

// Declaring Variables

```
double a;      // Declare a to be a double variable
int x, y;      // Declare x and y as integer variables
```

// Assignment Statements

```
a = 7.1;       // Assign 7.1 to a;
x = 1 + 3;     // assign 4 to x;
y = x + 2;     // assign 6 to y;
```

// Declaring and Initializing in ONE Step

```
double a2 = 7.1;
int x2 = 1, y2 = 2;
```


Using Variables

- Here are two more examples of two variables x and y

```
int x;           // declare a variable
x = 5;           // initialize a variable - what is assignment '='?
int y = 10;      // declare and initialize a variable
println(x);      // print value of x
x = 10;          // overwrite old value
println("x " + x); //what is the output?
```

```
int x = 10, y;   // y has no values yet
y = x;           // y is 10 now
y = y + 1;       // = does not mean equal, it means assignment.
println("x + y = " + (x + y)); //notice the output
```

Constants

- Constants are similar to variables except that once initialized they cannot change.
- To create a constant, use the keyword **final** before your variable declaration.

```
final double PI = 3.14159;  
final int SIZE = 3;
```

- Naming Convention:
 - Capitalize all letters in constants
 - e.g. **MAX**, **PI**, **SIZE**
 - Use underscores for multiple words.
 - e.g. **MAX_VALUE**



Expressions



The Assignment Statement

- An **assignment statement** changes the value of a variable.
 - The variable on the left-hand side of the **=** is assigned the value from the right-hand side.
 - The value may be changed to a constant, to the result of an expression, or to be the same as another variable.
 - The values of any variables used in the expression are always their values before the start of the execution of the assignment.

■ Example:

```
int A, B;  
A = 5;  
B = 10;  
A = 10 + 6 / 2;  
B = A;  
A = 2*B + A - 5;
```

Question: What are the values of A and B?

Expressions

- An **expression** is a sequence of operands and operators that yield a result. An expression contains:
 - **operands** - the data items being manipulated in the calculation
 - e.g. 5, "Hello, World", myDouble
 - **operators** - the operations performed on the operands
 - e.g. +, -, /, *, % (modulus or remainder after integer division)
- An operator can be:
 - **unary** - applies to only one operand
 - e.g. d = -3.5; // "-" is a unary operator, 3.5 is the operand
 - **binary** - applies to two operands
 - e.g. d = 3 * 5.0; // "*" is binary operator, 3 and 5.0 are operands
- **Integer Division:**
 - 5 / 2 if both operands are integers, the output is an integer 2
 - 5.0 / 2 if at least one operand is float, output is float 2.5

Division Operator

- What is the result of $25 / 4$?
- How would you rewrite the expression if you wished the result to be a floating-point number?
- Are the following statements correct? If so, show the output.

```
println("25 / 4 is " + 25 / 4);  
println("25 / 4.0 is " + 25 / 4.0);  
println("3 * 2 / 4 is " + 3 * 2 / 4);  
println("3.0 * 2 / 4 is " + 3.0 * 2 / 4);
```

The Remainder Operator (%)

- The % operator returns the remainder of two numbers.

- Examples:

<u>Operation</u>	<u>Result</u>
a) 14 % 6	2
b) -34 % 5	- 4 (matches numerator sign)
c) -34 % -5	- 4
d) 34 % -5	4
e) 5 % 1	0
f) 1 % 5	1
g) 3 % 0	runtime error. Can't divide by zero

Operator Precedence

- Each operator has its own priority similar to their priority in regular math expressions:
 - Any expression in parentheses is evaluated first starting with the inner most nesting of parentheses.
 - Unary + and unary - have the next highest priorities.
 - Multiplication and division ($*$, $/$, $\%$) are next.
 - Addition and subtraction ($+$, $-$) are then evaluated.

The ++ and -- Operators

- It is very common to subtract 1 or add 1 from the current value of an integer variable.
- There are two operators which abbreviate these operations:
 - ++ add one to the current integer variable
 - -- subtract one from the current integer variable
- Example:

```
var j=0;
```

```
j++;            // j = 1;    Equivalent to j = j + 1;
```

```
j--;            // j = 0;    Equivalent to j = j - 1;
```

Augmented Assignment

- The operators **+**, **-**, *****, **/**, and **%** can be combined with the assignment operator **=** to form augmented operators.

<code>x += 5;</code>	//Equivalent to	<code>x = x + 5</code>
<code>x -= 5;</code>	//Equivalent to	<code>x = x - 5</code>
<code>x *= 5;</code>	//Equivalent to	<code>x = x * 5</code>
<code>x /= 5;</code>	//Equivalent to	<code>x = x / 5</code>
<code>x %= 5;</code>	//Equivalent to	<code>x = x % 5</code>